



PREMIUM

NAŚWIETLACZE LED / LED FLOODLIGHTS

# LED MHNC 30W


## PREMIUM



141

38

107



- projektor oświetleniowy z mikrofalowym czujnikiem ruchu o trzech zakresach regulacji: czas działania, natężenie światła i zasięg detekcji,
- regulacja za pomocą pilota,
- czas działania: 10 sek, 30 sek, 1 min, 5 min, 8 min, 10 min,
- natężenie światła: wyłączony lub 1-10 lx, 10-30 lx, 30-70 lx, 70-150 lx,
- zasięg detekcji: max. 10 m oraz do 5 m i do 8 m,
- kąt detekcji: 120 stopni,
- kąt rozsyłu światła: 120 stopni,
- optymalna wysokość do montażu: 1,8 – 2,5 m,
- nie można wymieniać lamp w oprawie.

- lighting projector with microwave motion sensor of three ranges of adjustment: working time, light intensity and detection range,
- adjustment by a remote,
- working time: 10 sec, 30 sec, 1 min, 5 min, 8 min, 10 min,
- light intensity: off or 1-10 lx, 10-30 lx, 30-70 lx, 70-150 lx,
- detection range: max. 10 m and up to 5 m and to 8 m,
- detection angle: 120 degrees,
- beam angle: 120 degrees,
- optimal installation height: 1,8 – 2,5 m,
- lamps inside are unchangeable.

MODEL	INDEKS	POBÓR MOCY [W]	BARWA ŚWIATŁA	STRUMIEŃ ŚWIETLNY [lm]	WAGA NETTO [kg]	PAKOWANIE [szt.]	KOD EAN
MODEL	INDEX	POWER [W]	LIGHT COLOR	LUMINOUS FLUX [lm]	NET WEIGHT [kg]	PACKING [pcs.]	BARCODE
LED MHNC 30W NB	KFNLC30NB2	30	NEUTRALNA BIAŁA NEUTRAL WHITE	2700	0,42	30	5902201303735
LED MHNC 30W ZB	KFNLC30ZB2	30	ZIMNOBIAŁA COOL WHITE	2700	0,42	30	5902201303742

230V~

50Hz



IP 65



LED

4000K

6500K

25 000

cosφ PF≥0,90

Ra ≥80

20 000

-20°C  
40°C